



TECHNICAL DATASHEET

PVX Multimount®

Description

Multifunctional **wind certified** mounting system for installing mesh tray and / or tube on flat roofs. Top: mesh tray insertion area with possibility for 3 x wire mesh clip (s). Side: 2 x tube entry $\varnothing$ 16-32 mm + 2 x tube lockers on the top. Lid function for inserting tube. Coupling function for infinite width mounting of mesh tray.



Technical specifications

- Dimensions (mm): L 150 x W 115 x H 100
- Weight: 1120 gr
- Material: ASA, HDPE, Halogen free
- Maximum load: 50 KG
- Uv-stable: 100%
- Temperature: - 40°C to + 60°C
- BallasT Block: Frost resistant concrete, Komo certificated
- Verticale mounting: 2 x M6 mounting holes in bottom including rosette

Certification

Wind, in accordance with NEN-EN 1881-1-4: 2011, NEN 7250: 2014, CUR Recommendation 103: 2005.

Max wind force: 10 (24,5-28,4 m/s)

Article number

PVX23011945

Product warranty

15 year



PVX Mounting Systems®

Buitenbaan 70, NL-4206 VT Gorinchem, +31 (0)6-40235633

info@pvxmountingsystems.com | www.pvxmountingsystems.com