



TECHNICAL DATASHEET

PVX Singleroof® Flex 75 - 125

Description

The **PVX Singleroof 75 - 125** is a adjustable protective roof made of 1,5mm Magnelis® steel, part of **PVX Protection**, designed to protect components such as inverters and batteries from **direct weather exposure**.

Technical specifications

- Dimensions (cm): W 75 - 125 x D 45 x H 25
- Weight: 11 kg
- Material: Steel
- Protection layer: Magnelis (Zn-Al-Mg) - type ZM310
- Material thickness: 1.5mm
- Fire class: A1 in accordance with NEN-EN 13501-1
- Color: Zilver
- Application: Wall
- Box dimensions: L 75,5cm x D 45,5cm x H 25,5cm

Certification

Wind: designed and calculated for wind loads up to 32.8 m/s, in accordance with NEN-EN 1991-1-4:2011 (Eurocode), NEN 7250:2014 and CUR Recommendation 103:2005.

Article number

PVX13042015

Product warranty

15 years



PVX Mounting Systems
THE STANDARD IN CABLE MANAGEMENT

PVX Mounting Systems®

Handelskade 5.04, NL-4205 AC Gorinchem, +31 (0)6-40235633

info@pvxmountingsystems.com | www.pvxmountingsystems.com