PVX SINGLEROOF® FLEX 75–125
ON THE WALL. PROTECTED.

Article no. **PVX13042015** · Wall · Made in Holland



An extendable protective roof, mounted **on the wall** directly above the inverter, battery or other technical installation. Made of **1 mm steel with Magnelis® ZM310 coating**, self-healing at the cut edges.

Shields against direct rain, snow, UV radiation and dirt. **Fixing material included.**

> **Extendable from 75 to 125 cm.**
> Size not known in advance? One roof for every width.

TECHNICAL SPECIFICATIONS

Dimensions (L × D × H)	75 – 125 × 45 × 25 cm, extendable
Material	Steel, 1 mm
Coating	Magnelis® ZM310 (Zn-Al-Mg), self-healing at the cut edges
Weight	8.2 kg
Fixing points	7 – 9
Fixing material	Included, for concrete (C20/25), solid brick (MZ12) and solid sand-lime brick (KZ12). Other substrates: please contact us
Fire class	A1 according to NEN-EN 13501-1
Packaging	Per unit in a box, 76 × 46.5 × 28 cm; 12 per pallet

Wind load calculated

In accordance with NEN-EN 1991-1-4:2011, NEN 7250:2014 and CUR Recommendation 103:2005. Up to 27 m/s.

15-year warranty

Product and application warranty, provided installation follows the installation manual, using all fixing points.

Colours

Available in silver only.

PVX Mounting Systems®
Handelskade 5.04, NL-4205 AC Gorinchem · +31 (0)6-40235633
info@pvxmountingsystems.com · www.pvxmountingsystems.com

Technical datasheet EN
Version 2026.1
Subject to change.