PVX SHELTER® SINGLE
FREESTANDING. BALLASTED.

Article no. **PVX01142026** · Made in Holland



A freestanding mounting frame for inverters, batteries and other technical installations on flat roofs. **Ballasted, so no roof penetrations.**

The roof covers one side and shields against direct weather from above. **Both sides can be used**: on the other side you mount equipment that does not need a roof.

> **Fastest assembly on the market.**
> One person, ±30 minutes, 7 steps.

TECHNICAL SPECIFICATIONS

Dimensions (W × D × H)	1500 × 1530 × 1615 mm
Load capacity	115 kg per side
Weight	48 kg
Material frame and roof	Magnelis® ZM310
Bolts and nuts	M10, stainless steel
Mounting beams (2 pcs)	1× PVX Drop-Stop (lip as anti-slip safeguard), 1× standard
Use	Both sides usable, roof over one side
Ballast	Not included; see ballast table in the installation manual
Packaging	Per unit in a wooden frame, 175 × 55 × 85 cm

Wind certified

By Peutz. In accordance with NEN-EN 1991-1-4:2011, NEN 7250:2014 and CUR Recommendation 103:2005.

15-year warranty

Product and application warranty, provided installation follows the installation manual and the ballast table.

Watch the installation video
Scan or click

PVX Mounting Systems®
Handelskade 5.04, NL-4205 AC Gorinchem · +31 (0)6-40235633
info@pvxmountingsystems.com · www.pvxmountingsystems.com

Technical datasheet EN
Version 2026.1
Subject to change.