PVX MULTISTRAP+®
FREE-STANDING. BALLASTED.

Article no. **PVX18051993** · Flat roof · Made in Holland



Mounting system for **tubes or M8 applications on flat roofs**. Cable ties for tubes and a pre-mounted M8 bolt with nut are supplied.

With its own ballast block it is placed directly on the roof, **without drilling or roof penetrations**.

> **Tube and M8, everything included.**
> Tube up to Ø 100 mm? Add your own 4.8 mm wide cable ties.

TECHNICAL SPECIFICATIONS

Dimensions (L × W × H)	168 × 107 × 75 mm
Tube	2 × Ø 16 – 32 mm or 1 × Ø 16 – 100 mm
M8 application	Max. 300 mm wide
Max. load per support	125 kg, incl. snow load
Weight	1.12 kg
Material	HDPE, halogen-free, 100% UV-stable
Supplied	2 × cable tie 200 × 4.8 mm (max. Ø 50 mm, 24 years UV-stable) and 1 × pre-mounted M8 bolt with nut, hot-dip galvanised
Max. tensile force cable tie	22 kg
Ballast block	1×, frost-resistant concrete, KOMO® certified, 100-year warranty
Direct placement on	Bitumen, PVC, TPO, EPDM, concrete, etc.
Temperature	-40 °C to +60 °C
Packaging	Box of 20 pcs, 55.5 × 35.5 × 17.5 cm, approx. 23 kg

Wind certified

By consultancy Peutz. In accordance with NEN-EN 1991-1-4:2011, NEN 7250:2014 and CUR Recommendation 103:2005. Up to wind force 10 (24.5–28.4 m/s).

15-year warranty

Product and application warranty, provided installation follows the installation manual and the support distance is approved by the PVX Calculator.

Watch the installation videos
Scan or click

PVX Mounting Systems®
Handelskade 5.04, NL-4205 AC Gorinchem · +31 (0)6-40235633
info@pvxmountingsystems.com · www.pvxmountingsystems.com

Technical datasheet EN
Version 2026.1
Subject to change.