PVX MULTIMOUNT®
FREE-STANDING. BALLASTED.

Article no. **PVX23011945** · Flat roof · Made in Holland



The all-round mounting system for **mesh trays and tubes on flat roofs**, can be coupled to any width.

With its own ballast block it is placed directly on the roof, **without drilling or roof penetrations**.

> **Simply... Click & Go.**
> Mesh tray and tube in one system, for all brands.

TECHNICAL SPECIFICATIONS

Dimensions (L × W × H)	150 × 115 × 100 mm
Mesh tray	60 – 300 mm wide, room for 3 mesh tray clips
Tube	2 × tube entry Ø 16 – 32 mm, with tube lockers and lid function
Max. load per support	125 kg, incl. snow load
Weight	1.12 kg
Material	ASA, HDPE, halogen-free, 100% UV-stable
Ballast block	1×, frost-resistant concrete, KOMO® certified, 100-year warranty
Coupling function	Can be coupled to any width
Vertical mounting	2 × M6 drill hole in the base, incl. rosette
Direct placement on	Bitumen, PVC, TPO, EPDM, concrete, etc.
Grid dimensions	Check before use, see installation manual
Temperature	-40 °C to +60 °C
Packaging	Box of 20 pcs, 60 × 33 × 23 cm, approx. 23 kg

Wind certified

By consultancy Peutz. In accordance with NEN-EN 1991-1-4:2011, NEN 7250:2014 and CUR Recommendation 103:2005. Up to wind force 10 (24.5–28.4 m/s).

15-year warranty

Product and application warranty, provided installation follows the installation manual and the support distance is approved by the PVX Calculator.

Watch the installation videos
Scan or click

PVX Mounting Systems®
Handelskade 5.04, NL-4205 AC Gorinchem · +31 (0)6-40235633
info@pvxmountingsystems.com · www.pvxmountingsystems.com

Technical datasheet EN
Version 2026.1
Subject to change.