PVX MINIFIX®
SCREWED. WATERTIGHT.

Article no. **PVX05102025** · Pitched roof & wall · Made in Holland



Mounting system for installing **M8 applications on pitched roofs and walls**. The Minifix is screwed directly onto the roof or façade and, thanks to the EPDM seal, **can be installed watertight**.

On top there is an M8 bolt for mounting the application.

> **M8 bolt on top.**
> For M8 applications up to 200 mm wide.

TECHNICAL SPECIFICATIONS

Dimensions (L × W × H)	95.8 × 79.9 × 30 mm
M8 application	Up to 200 mm wide
Max. load per support	250 kg, incl. snow load
Weight	25 g
Material	Nylon PA6GF30, halogen-free, UV-stable
Colour	Black
Application	Pitched roof, wall
Watertight installation	EPDM
Fixing	Screw Ø 6.3 mm with EPDM sealing washer (not supplied)
Temperature	-40 °C to +100 °C
Packaging	Box of 36 pcs, 39.2 × 24.8 × 10.3 cm, approx. 1.1 kg

Wind certified

By consultancy Peutz. In accordance with NEN-EN 1991-1-4:2011, NEN 7250:2014 and CUR Recommendation 103:2005. Up to wind force 10 (24.5–28.4 m/s).

15-year warranty

Product and application warranty, provided the support distance is approved by the PVX Calculator.

Watch the installation videos
Scan or click

PVX Mounting Systems®
Handelskade 5.04, NL-4205 AC Gorinchem · +31 (0)6-40235633
info@pvxmountingsystems.com · www.pvxmountingsystems.com

Technical datasheet EN
Version 2026.1
Subject to change.