PVX Mounting Systems
THE STANDARD IN CABLE MANAGEMENT

PRODUCT OVERVIEW 2026

PVX PROTECTION

Protection for inverters, batteries and other technical installations, on the wall and on the flat roof.



PVX Singleroof® 100 in practice

SELECTION GUIDE

WHERE DOES THE INSTALLATION GO, AND WHAT SIZE?


Pick the row for the location, then the column that fits.

	SIZE KNOWN	SIZE NOT YET KNOWN	PROTECTION
Wall	● Singleroof 75 ● 100 ● 150	● Singleroof Flex 75–125	Roof above the installation
Flat roof	● Shelter single roof ● Shelter double roof	One fixed roof width: 1500 mm	Free-standing frame with roof

WALL · PVX SINGLEROOF®

A ROOF OVER YOUR INSTALLATION


Fixing materials included, for concrete, solid brick and sand-lime brick. Always use all fixing points.



SINGLEROOF® 75

FIXED SIZE · 75 CM


Size (cm)	75 × 45 × 25
Steel	1.5 mm
Weight	6.7 kg
Fixing pts	7
Per pallet	12
Wind up to	33.8 m/s
Item no.	PVX01052026



SINGLEROOF® 100

FIXED SIZE · 100 CM


Size (cm)	100 × 45 × 25
Steel	1.5 mm
Weight	8.9 kg
Fixing pts	8
Per pallet	8
Wind up to	33.8 m/s
Item no.	PVX10052026



SINGLEROOF® 150

FIXED SIZE · 150 CM

Size (cm)	150 × 45 × 25
Steel	1.5 mm
Weight	13.5 kg
Fixing pts	9
Per pallet	6
Wind up to	33.8 m/s
Item no.	PVX15052026



SINGLEROOF® FLEX

EXTENDABLE 75–125

Size (cm)	75–125 × 45 × 25
Steel	1 mm
Weight	8.2 kg
Fixing pts	7–9
Per pallet	12
Wind up to	27 m/s
Item no.	PVX13042015

Colours from stock (75 · 100 · 150) Silver · RAL 7016 anthracite grey · RAL 9016 traffic white

Other RAL colour on request

FLAT ROOF · PVX SHELTER

FREE-STANDING. BALLASTED.

Mounting frame with ballast carriers, without roof penetrations. Ballast not included.



SHELTER

SINGLE ROOF

Both sides usable, roof on one side

Roof width	1500 mm
Max. per side	115 kg
Weight	49 kg
Parts	10
Installation	1 person · ±30 min
Item no.	PVX01142026



SHELTER

DOUBLE ROOF

Both sides usable, roof over both sides

Roof width	1500 mm
Max. per side	115 kg
Weight	58 kg
Parts	11
Installation	1 person · ±30 min
Item no.	PVX02132026

MORE INFORMATION

SCAN THE QR CODE

Support wall
Manuals and videos

Support flat roof
Manuals and ballast table

Website
pvxmountingsystems.com

Wind certified
Singleroof calculated according to NEN-EN 1991-1-4. Shelter wind certified by Peutz.

Magnelis® ZM310
Coated steel, self-healing at cut edges.

15-year warranty
Product and application warranty, provided it is installed according to the installation manual.

Made in Holland
Developed and manufactured by PVX Mounting Systems.